

DELTA PREMIUM 2322




ADVANTAGES



Pronounced power dissipation



Gentle on containers thanks to double pallet truck support



High ground clearance thanks to automatic lifting of the lifting carriage when moving on



Optimised emptying behaviour thanks to active container retention



ABOUT THE DELTA PREMIUM 2322

In conjunction with a MEDIUM X2 or MEDIUM X4 rear-end loader, the new automatic lifter with two independently operating lifting and tipping units with lifting comb and a flexible installation range of 1150 to 1550 mm offers an optimum standing position with the best

possible positioning and shoulder clearance as well as preparation for additional cameras for footboard monitoring. Also included: a new barrier design – optionally extendable for fully automatic emptying of 4-wheel bins. Perfectly suited for residential areas –

can also be optimally operated by one person. The special feature of the DELTA 2322: the Diamond front pick-up.

SERIES OPTIONS

BASIC CONSTRUCTION:

- DIN version
- Automatic and manual actuation
- Split and continuous comb holder
- Preparation for weighting and RFID systems
- Weight optimisation through various lifting carriage devices
- Compatible with vehicle widths 2300 mm and 2500 mm

t

COMPLEMENTED BY SAFETY & ASSISTANCE SYSTEMS:

- Deep Scan
- Worker Protection System
- Safety equipment

Further information

