



### Container types

Container range depending on model	Wheeled bin	Wheeled bin	Container	Container
Specification in accordance with model list	80/120L	140/240L	500-1200L	770-1300L
Special containers upon request	EN 840-1	EN 840-1	EN 840-2	EN 840-3

### Lifter dimensions in mm

<b>a</b> Setting height	860	860	900	900
<b>b</b> Ground clearance	450	450	490	490
<b>c</b> Installation height	1315	1315	1315	1315
<b>d</b> Installation widths (RCV widths)	1780- 2260			
<b>e</b> Total width of lifters	d + 300			

### Technical data

Cycle time*	app. 9 s	app. 9 s	app. 12 s	app. 12 s
Lifting and tipping capacities**	3500 N	3500 N	7000 N	7000 N
Noise level***	72 dB(A)	72 dB(A)	72 dB(A)	72 dB(A)
Hydraulic flow at coupling	30 - 36 l/min			
Operating pressure	150-190 bar			
Operating voltage	24 V			
Weight	app. 450 kg			

### Legend

- \* Cycle time (without dwell time) depends on installation height and container size.
- \*\* Lifting and tipping capacities refer to max. use of nominal container capacity with a refuse density of 0.4 kg/dm<sup>3</sup>.
- \*\*\* Data relating to working area w/o container.
- \*\*\*\* Position of lifter gravity centre with swinging arm lowered.



**ZOELLER**<sup>®</sup>